

WHERE TO BE USED:

Fair Face Walls | Partitioning Walls | Load Bearing Walls | Boundary Walls | Decorative Application

COLOUR RANGE:





Grev

Customized

LAYING PATTERNS







SPECIAL FEATURES

- Manufactured in 100% Automated Plant with technology from Germany
- Easy year round installation
- Cured in heat and humidity controlled curing chamber
- Excellent skid resistance

ADVANTAGES

- Rapid Execution of Work: Asian Hollow Blocks are lighter and of uniform size. This facilitates rapid execution.
- Increase in Floor Area: Option to build thinner walls helps save space and increase floor area.
- Reduces Construction Cost: Asian Hollow Blocks helps save construction material and reduces constructions cost.
- **Better Insulation:** Offers great insulation against sound, heat and dampness.
- More Durable: Asian Hollow Blocks withstands atmospheric turmoil and requires no protective covering.
- Bonding of Mortar & Plaster: Rough surface provides good bonding of mortar and plaster.

SPECIFICATIONS

Hollow Block (in)	Dimensions (mm) (Length x Breadth x Thickness)	Blocks/m²	Blocks/ft²	Compressive Strength (MPa)
4	390 x 100 x 190	13.49	1.25	≥7.5
6	390 x 150 x 190	13.49	1.25	≥7.5
8	390 x 200 x 190	13.49	1.25	≽7.5

ASIAN CONCRETO LTD.







SALES OFFICE:

1st Floor, ShriPri Home, Kalikasthan -29, Kathmandu, Nepal. Phone: +977-9802711199 Email: info@asianconcreto.com

FACTORY:

Hakui, Ramgram-16, Nawalparasi, Nepal. Phone: +977-9802711199 Email: info@asianconcreto.com

SALES INQUIRY:

Phone (Nepal): +977-9802711199
Phone (India): +91-9335802209
Email: info@asianconcreto.com
Website: www.asianconcreto.com
Follow Us On: