

- Manufactured in 100% Automated Plant with technology from Germany
- Easy, year round installation
- Cured in heat and humidity controlled curing chamber
- Excellent skid resistance

Advantages:

- · Cost-effective, less time-consuming
- High resistance to wear and mechanical damage
- Reusable and can be installed swiftly

Where to be used:

Walkways | Driveways | Patios | Garden Areas | Pool Decks | Terrace | House Colonies

Colour Range:

















Mix Blended Customized

Laying Patterns:





Specifications:

Parameters	Dimensions
Length (mm)	200
Width (mm)	200
Thickness (mm)	60
Pavers/m²	25
Pavers/ft²	2.32
Compressive Strength (N/mm²)	≥ 45

Load Factor:











ASIAN CONCRETO PVT. LTD.







INDIA SALES OFFICE:

Plot No. 84, Palm Paradise, Ramgarh Taal, Gorakhpur, UP, India Phone: +91-8127585858

NEPAL SALES OFFICE:

1st Floor, ShriPri Home, Kalikasthan - 29, Kathmandu, Nepal Phone: +977-9802711199

FACTORY:

Ramgram - 16 Nawalparasi, Nepal. Phone: +977-9802711199 Email: info@asianconcreto.com Website: www.asianconcreto.com Follow us on 📑 💿 🕞 in Asian Concreto Pvt. Ltd.