

WHERE TO BE USED:

Sidewalks | Walkways | Parks | Patios | Driveways

COLOUR RANGE:













Black





LOAD FACTOR:











SPECIAL FEATURES

- Manufactured in 100% Automated Plant with technology from Germany
- Easy year round installation
- Cured in heat and humidity controlled curing chamber
- Excellent skid resistance

ADVANTAGES

- Cost-effective, less time-consuming
- High resistance to wear and mechanical damage
- Reusable and can be installed swiftly
- Used to create one-of-a-kind landscape designs

SPECIFICATIONS

Dimensions (mm) (Length x Breadth x Thickness)	Pavers/m²	Pavers/ft²	Compressive Strength (MPa)
200 x 200 x 60	26.66	2.48	≽35

LAYING PATTERNS













ASIAN CONCRETO LTD.







SALES OFFICE:

1st Floor, ShriPri Home, Kalikasthan -29, Kathmandu, Nepal. Phone: +977-9802711199

Email: info@asianconcreto.com

FACTORY:

Hakui, Ramgram-16, Nawalparasi, Nepal. Phone: +977-9802711199 Email: info@asianconcreto.com

SALES INQUIRY:

Phone (Nepal): +977-9802711199 Phone (India): +91-9335802209 Email: info@asianconcreto.com Website: www.asianconcreto.com Follow Us On: 📝 🎯 🔼 🛅