

SPECIAL FEATURES

technology from Germany Easy year round installation

Excellent skid resistance

Cost-effective, less time-consuming

Reusable and can be installed swiftly

ADVANTAGES

• Manufactured in 100% Automated Plant with

Cured in heat and humidity controlled curing chamber

• High resistance to wear and mechanical damage

• Used to create one-of-a-kind landscape designs

WHERE TO BE USED:

Parking Areas | Driveways | Rural and Community Roads | Housing Colonies | Large Scale Industrial Areas | Heavy Traffic Load Bearing Areas

COLOUR RANGE:





LOAD FACTOR:











Mix Blended















SPECIFICATIONS

Dimensions (mm) (Length x Breadth x Thickness)	Pavers/m²	Pavers/ft ²	Compressive Strength (MPa)
225 x 112.5 x 80	40.36	3.75	≽40
225 x 112.5 x 100	40.36	3.75	≥50

LAYING PATTERNS













ASIAN CONCRETO LTD.







SALES OFFICE:

1st Floor, ShriPri Home. Kalikasthan -29, Kathmandu, Nepal. Phone: +977-9802711199 Email: info@asianconcreto.com

FACTORY:

Hakui, Ramgram-16, Nawalparasi, Nepal. Phone: +977-9802711199 Email: info@asianconcreto.com

SALES INQUIRY:

Phone (Nepal): +977-9802711199 Phone (India): +91-9335802209 Email: info@asianconcreto.com Website: www.asianconcreto.com Follow Us On: 🜃 💿 📭 in