

- · Manufactured in 100% Automated Plant with technology from Germany
- Easy, year round installation
- · Cured in heat and humidity controlled curing chamber
- Excellent skid resistance

Advantages:

- · Cost-effective, less time-consuming
- · High resistance to wear and mechanical damage
- · Reusable and can be installed swiftly

Where to be used:

Walkways | Driveways | Patios | Garden Areas | Pool Decks | Terrace | House Colonies

Colour Range:
















Laying Patterns:





200 mm

Parameters	Dimensions
Length (mm)	200
Width (mm)	200
Thickness (mm)	60
Pavers/m²	25
Pavers/ft²	2.32
Compressive Strength (N/mm²)	≥ 45

Load Factor:











200 mm

60 mm

ASIAN CONCRETO PVT. LTD.







INDIA SALES OFFICE:

Plot No. 84, Palm Paradise, Ramgarh Taal, Gorakhpur, UP, India Phone: +91-8127585858

NEPAL SALES OFFICE:

1st Floor, ShriPri Home, Kalikasthan - 29, Kathmandu, Nepal Phone: +977-9802711199

FACTORY:

Ramgram - 16 Nawalparasi, Nepal. Phone: +977-9802711199 Email: info@asianconcreto.com Website: www.asianconcreto.com Follow us on 📑 🎯 🕟 🛅 Asian Concreto Pvt. Ltd.